



## TERMINAL SPECIFICATIONS SUPERMARITIME NEDERLAND B.V. VLISSINGEN

### 1. Terminal

Operational	: 1 April 2013
Security	: 8 x CCTV – web connected cameras fenced / ISPS & AEO certified
Quay space	: 1 x 160 mtr / 8 mtr draft LLWS : 1 x 200 mtr / 14 mtr draft LLWS
Outside storage capacity	: 60.000 m2
Max. floorload outside	: 10 m/ton per m2



### 2. Warehouse

Surface	: 12.600 m2
Max floorload inside	: 10 m/ton per m2
Max workable ceiling hght:	17 mtr
Pallet racking	: 420 palletplaces
Entry doors	: 11 revolving doors: 6*6 mtr LxH : 1 main sectional door: 15*8 mtr LxH
Dock shelters	: 2 x
Power	: 12 x Heavy duty power plugs 380 kv
Security	: 2 moving dome CCTV-camera's
Fire protection	: 6 x water curtains



### 3. Handling Equipment

Crane capacity	: 3 x 100 m/ton Gottwald (mobile) : 1 x 20 m/ton Gottwald (mobile)
Container Reachstackers	: 1 x 38 m/ton Kalmar : 1 x 45 m/ton Kalmar
Forklift Trucks	: Various types of forklifts min. 2 ton electrical / max 25 ton diesel Various types of clamps, spreaders, slings and baskets



### 4. Other facilities

- The entire terminal can be used as a customs bonded area
- In-house operated packing & crating facility
- Line items checking & receiving facility in warehouse
- Own lashing & securing team for container & gen.cargo vessels
- Permanent availability of welding equipment / welders
- Preservation & conditioning programs & equipment available
- 24 Mtr truck weighbridge onsite
- Warehouse scale max. 1000 kgs
- Onsite office facilities available to clients.
- Containeryard with 50 reeferplug connections
- Entire terminal wifi connected

