



TERMINAL SPECIFICATIONS SUPERMARITIME NEDERLAND B.V. VLISSINGEN

Terminal

Operational : 1 April 2013
Terminal size : 90.000 sqm / 968.751 sqf
Security : 8 x CCTV – web connected cameras
Electrically fenced – a.o.h manned security patrols
ISPS & AEO certified
Quay space : 1 x 160 mtr / 8 mtr draft LLWS
: 1 x 200 mtr / 14 mtr draft LLWS
Outside storage capacity : 60.000 m2
Max. floorload outside : 10 m/ton per m2



Warehouse

Surface : 12.600 m2
Max floorload inside : 10 m/ton per m2
Max workable ceiling hght : 17 mtr
Pallet racking : 420 palletplaces
Entry doors : 11 revolving doors: 6*6 mtr LxH
: 1 main sectional door: 15*8 mtr LxH
Loading docks : 2 x lowered docks
Power : 12 x Heavy duty power plugs 380 kv
Security : moving dome CCTV-camera's
IT-connectivity : WIFI throughout warehouse
Glassfibre cable in warehouse connected to office
Fire protection : 6 x water curtains



Handling Equipment

Crane capacity : 3 x 100 m/ton Gottwald (mobile)
: 1 x 20 m/ton Gottwald (mobile)
Container Reachstackers : 1 x 38 m/ton Kalmar
: 1 x 45 m/ton Kalmar
Forklift Trucks : Various types of forklifts
min. 2 ton electrical / max 25 ton diesel
Various types of clamps, spreaders,
slings and baskets



Other facilities / features

- The entire terminal can be used as a customs bonded area
- In-house operated packing & crating facility
- Line items checking & receiving facility in warehouse
- Own lashing & securing team for container & gen.cargo vessels
- Permanent availability of welding equipment / welders
- Preservation & conditioning programs & equipment available
- 24 Mtr truck weighbridge onsite / warehouse scale max. 1000 kgs
- Mobile / floating crane availability locally for heavy lifts (3300ts)
- Onsite office facilities available to clients
- Containeryard / freight station with 36 reeferplug connections
- Railway and inland barge loading facility

